



QuickSeam™ FormFlash™

Firestone Item Number:

W56RAC1650: 228.6 mm x 15.2 m (9.0" x 50.0') rolls

W56RAC1652: & 304.8 mm x 15.2 m (12.0" x 50.0') rolls

W56RAC1653:

DESCRIPTION:

Firestone QuickSeam FormFlash is an uncured EPDM flashing laminated to cured seam tape. QuickSeam FormFlash is used to flash inside and outside corners, pipes, penetration pockets and other applications as required by Firestone Specialty Products specifications and details.

METHOD OF APPLICATION:

1. Use QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus™ pad and handle to clean and prime mating surfaces.
2. When cloudy conditions below 15.6° C (60° F) occur, use heat guns (without ignition sources) to heat QuickSeam FormFlash. This will ensure good formability of the QuickSeam FormFlash to the primed substrate.
3. On sunny days less than 21.1° C (70° F), lay out QuickSeam FormFlash (prior to application) with flashing side up to allow QuickSeam FormFlash to warm to ensure good formability.
4. On sunny days greater than 21.1° C (70° F), lay out QuickSeam FormFlash (prior to application) with release paper side up to prevent QuickSeam FormFlash from gaining too much heat and to ensure good formability.

SHELF LIFE:

1. Shelf life of one (1) year can be expected if stored in original unopened container at temperatures between 15.6 - 26.7° C (60 - 80° F).
2. Shelf life will be shortened if exposed to elevated temperatures.
3. Rotate stock to insure stored material will not go beyond the shelf life of one (1) year.

STORAGE:

1. Store in original unopened containers at temperatures between 15.6 - 26.7° C (60 - 80° F) until ready for use.



PRODUCT DATA

<u>Property</u>	<u>Minimum Performance</u>
<u>QuickSeam Tape</u>	
Base:	Rubber Polymer
Color:	Black
Solvents:	None
Solids:	100%
Cured State:	Cured
Thickness:	0.635 mm +/- 0.18 mm (0.025" +/- 0.007")
<u>EPDM Flashing</u>	
Base:	EPDM
Color:	Black
Solvents:	None
Solids:	100%
Cured State:	Uncured
Thickness:	1.6 mm +/- 0.13 mm (0.065" +/- 0.005")

Physical Characteristics:

1. Excellent moisture resistance.
2. Excellent resistance to heat and cold
3. Excellent green tack.

STORAGE (Con't):

2. When exposed to lower temperatures, restore to room temperature prior to use.
3. Keep the material out of direct sunlight until ready for application.

PACKAGING:

<u>SI</u>		<u>Eng</u>		<u>Rolls/</u>	<u>Cartons/</u>
<u>Width</u>	<u>Length</u>	<u>Width</u>	<u>Length</u>	<u>Carton</u>	<u>Pallet</u>
228.6 mm	15.2 m	9.0"	50.0'	2	40
304.8 mm	15.2 m	12.0"	50.0'	1	48

QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

PRECAUTIONARY DATA:

Review Material Safety Data Sheet (MSDS) prior to use.

LEED INFORMATION:

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Prescott, AR
Michigan Center, MI

Note: FormFlash is protected under U.S. Patent Number 5,804,661.

Firestone
SPECIALTY PRODUCTS

QuickSeam FormFlash

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice design, Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any project on which its products may be applied. If questions arise as to the soundness of a project, or its ability to support a planned installation properly, the Owner should obtain opinions of competent design engineers before proceeding. Firestone accepts no liability for any failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

Firestone Specialty Products
250 West 96th Street, Indianapolis, Indiana 46260
Specialty Products (800) 428-4442
Internet Address: <http://www.firestonesp.com>