

## EasySealant



### 1. Description

The Firestone EasySealant is a superior quality sealant-adhesive based on MS polymer. It is designed to seal, adhere and repair GeoSmart EPDM membranes installed in small water ponds. The EasySealant will ensure a strong and durable watertight connection to different types of substrates (EPDM to EPDM, wood, metal, concrete, stones, etc.).

### 2. Preparation

Surfaces on which the EasySealant is to be applied must be smooth, clean, and free from dust, oil and grease. Restore to room temperature prior to use, if exposed to lower temperatures (< 15°C) for a prolonged period.

### 3. Application

The sealant is applied with a mastic gun at the specified location. Cut the applicator nozzle with a cutter in order to have a 7 mm diameter opening. Apply a constant line of sealant at a speed of  $\pm 6s/10cm$ . Close and softly roll the top liner. Wait minimum 48 hours (longueur in cold temperatures) before applying moderate tension onto the detail. For more detailed information, refer to the specific Firestone application guide.

### 4. Coverage

Coverage rate of  $\pm 6$  lm per cartridge (bead width of 6 mm).

### 5. Characteristics

Physical	
• Black liquid paste	
Technical	
• Base	1,2-Ethanediamine,N-,3-,trimethoxysilyl,propyl
• Color	Black
• Solvents	none
• Solids	100%
• Flash Point	> 100 °C

### 6. Packaging / Storage / Shelf Life

Packaging	12 cartridges/carton
Part numbers	NA

**Storage:** Store in original unopened containers at temperatures between 15°C and 25°C in a dry, well-ventilated area. Keep the material out of direct sunlight until ready for application.

**Shelf Life:** 12 months, when stored in above-mentioned conditions. Shelf life will be reduced if exposed to higher temperatures.

### 7. Precautions

Refer to Safety Data Sheet. Avoid contact with skin and eyes. Do not contaminate with foreign materials. Keep out of the reach of children. Recommended cleaner is Firestone Cleaner followed by soap and water.

This document replaces any other document published previously. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.